



AD910J

Kombinētais automāts 6kA 2P B 10A 30mA, A - tips

Zīmols: Hager

GTIN: 3250611040699

Kombinētais automāts 6kA 2P B 10A 30mA, A - tips

ETIM dati:

| | |
|--|--|
| Number of poles (total) | 2 |
| Number of protected poles | 1 |
| Rated voltage | 240 V |
| Rated insulation voltage U_i | 500 V |
| Rated impulse withstand voltage U_{imp} | 4 kV |
| Rated current | 10 A |
| Rated fault current | 0.03 A |
| Leakage current type | A |
| Current limiting class | 3 |
| Rated short-circuit breaking capacity according to IEC 60947-2 | 6 kA |
| Rated short-circuit breaking capacity I_{cn} according to EN 61009-1 | 6 kA |
| Disconnection characteristic | Undelayed |
| Surge current capacity | 0.25 kA |
| Voltage type | AC |
| Frequency | 50 Hz |
| Release characteristic | B |
| Concurrently switching neutral conductor | Yes |
| With interlocking device | No |
| Over voltage category | 3 |
| Pollution degree | 2 |
| Ambient temperature during operating | -25 °C - 40 °C |
| Width in number of modular spacings | 2 |
| Built-in depth | 68 mm |
| Flush-mounted installation | Jā |
| Anti-nuisance tripping version | No |
| Degree of protection (IP) | IP20 |
| Connectable conductor cross section solid-core | 1 mm ² - 25 mm ² |
| Connectable conductor cross section multi-wired | 1 mm ² - 16 mm ² |

Apstiprinājumi / marķējumi:

