



AD966B

**RVK+Kaitselül. 1P+N 6kA 16A "C" 30mA -"AC"**

**Bränd:** Hager

**GTIN:** 3250611040194

RVK+Kaitselül. 1P+N 6kA 16A "C" 30mA -"AC"

**ETIM-teave:**

Pooluste arv (kokku)	2
Kaitstud pooluste arv	1
Tunnuspinge	240 V
Isolatsiooni nimipinge Ui	500 V
Tunnus-impulssaluvuspinge Uimp	4 kV
Tunnusvool	16 A
Rated fault current	0.03 A
Leakage current type	AC
Current limiting class	3
Rated short-circuit breaking capacity according to IEC 60947-2	6 kA
Rated short-circuit breaking capacity Icn according to EN 61009-1	6 kA
Disconnection characteristic	Undelayed
Surge current capacity	0.25 kA
Pinge liik	AC
Frequency	50 Hz
Vabasti tunnusjoon	C
Concurrently switching neutral conductor	Yes
With interlocking device	No
Over voltage category	3
Pollution degree	2
Ambient temperature during operating	-25 °C - 40 °C
Width in number of modular spacings	2
Sisseehitussügavus	68 mm
Flush-mounted installation	Jah
Anti-nuisance tripping version	No
Degree of protection (IP)	IP2X
Connectable conductor cross section solid-core	1 mm <sup>2</sup> - 25 mm <sup>2</sup>
Connectable conductor cross section multi-wired	1 mm <sup>2</sup> - 16 mm <sup>2</sup>

**Kinnitused / märgistused:**

