



ADA210N

2P RVK+Kaitselül. 10kA B-10A 30mA A Class

Bränd: Hager

GTIN: 3250611027096

2P RVK+Kaitselül. 10kA B-10A 30mA A Class

ETIM-teave:

Kaitstud pooluste arv	2
Tunnuspinge	230 V
Isolatsiooni nimipinge Ui	500 V
Tunnus-impulssaluvuspinge Uimp	4000 kV
Tunnusvool	10 A
Rated fault current	0.03 A
Leakage current type	A
Current limiting class	3
Rated short-circuit breaking capacity according to IEC 60947-2	10 kA
Rated short-circuit breaking capacity Icn according to EN 61009-1	10 kA
Disconnection characteristic	Undelayed
Pinge liik	AC
Frequency	50 Hz
Vabasti tunnusjoon	B
Concurrently switching neutral conductor	No
With interlocking device	No
Over voltage category	3
Pollution degree	2
Ambient temperature during operating	-25 °C - 40 °C
Width in number of modular spacings	2
Sisseehitussügavus	68 mm
Flush-mounted installation	Ei
Anti- nuisance tripping version	No
Degree of protection (IP)	IP2X
Connectable conductor cross section solid-core	1.5 mm ² - 25 mm ²
Connectable conductor cross section multi-wired	1.5 mm ² - 16 mm ²

Kinnitused / märgistused:

