



ADA556D

### Kombinētais automāts 10kA C-6A 30mA, A - tips

**Zīmols:** Hager

**GTIN:** 3250611067801

Kombinētais automāts 10kA C-6A 30mA, A - tips

#### ETIM dati:

Number of poles (total)	2
Number of protected poles	1
Rated voltage	240 V
Rated insulation voltage $U_i$	500 V
Rated impulse withstand voltage $U_{imp}$	4 kV
Rated current	6 A
Rated fault current	0.03 A
Leakage current type	A
Current limiting class	3
Power loss	1.9 W
Rated short-circuit breaking capacity according to IEC 60947-2	10 kA
Rated short-circuit breaking capacity $I_{cn}$ according to EN 61009-1	10 kA
Disconnection characteristic	Undelayed
Surge current capacity	0.25 kA
Voltage type	AC
Frequency	50 Hz
Release characteristic	C
Concurrently switching neutral conductor	Yes
With interlocking device	Yes
Over voltage category	3
Pollution degree	2
Ambient temperature during operating	-25 °C - 40 °C
Width in number of modular spacings	2
Built-in depth	68 mm
Flush-mounted installation	Jā
Anti-nuisance tripping version	No
Connectable conductor cross section solid-core	1 mm <sup>2</sup> - 25 mm <sup>2</sup>
Connectable conductor cross section multi-wired	1 mm <sup>2</sup> - 16 mm <sup>2</sup>

#### Apstiprinājumi / marķējumi:

