



ADA566D

RVK+Kaitselül. 1P+N 10kA 16A "C" 30mA -"A"

Bränd: Hager

GTIN: 3250611067832

RVK+Kaitselül. 1P+N 10kA 16A "C" 30mA -"A"

ETIM-teave:

Pooluste arv (kokku)	2
Kaitstud pooluste arv	1
Tunnuspinge	240 V
Isolatsiooni nimipinge U_i	500 V
Tunnus-impulssaluvuspinge U_{imp}	4 kV
Tunnusvool	16 A
Rated fault current	0.03 A
Leakage current type	A
Current limiting class	3
Power loss	5.2 W
Rated short-circuit breaking capacity according to IEC 60947-2	10 kA
Rated short-circuit breaking capacity I_{cn} according to EN 61009-1	10 kA
Disconnection characteristic	Undelayed
Surge current capacity	0.25 kA
Pinge liik	AC
Frequency	50 Hz
Vabasti tunnusjoon	C
Concurrently switching neutral conductor	Yes
With interlocking device	Yes
Over voltage category	3
Pollution degree	2
Ambient temperature during operating	-25 °C - 40 °C
Width in number of modular spacings	2
Sisseehitussügavus	68 mm
Flush-mounted installation	Jah
Anti- nuisance tripping version	No
Connectable conductor cross section solid-core	1 mm ² - 25 mm ²
Connectable conductor cross section multi-wired	1 mm ² - 16 mm ²

Kinnitused / märgistused:

