



A problem has occurred

2026-06-24 05:19:57

Error message:

This license has expired on 2026-05-30.

License Information:

| | |
|------------------------|---|
| License serial no: | 3916 |
| Licensee: | Adeona Oy |
| Product: | PDFReactor Web Service |
| Version: | 12.0 |
| License Type: | CPU |
| Amount: | 12 Thread(s) |
| Maintenance Exp. Date: | 2026-05-30 |
| Expiration Date: | 2026-05-30 |
| Purchase Date: | 2015-11-18 |
| Conditions: | [This license is for use on development systems only. It may not be used on staging or productive systems of any kind.] |
| Sign Date: | 2025-06-02 15:12 |



ADM420C

RVK + kaitselüliti 4P, 6kA, B-20A, 30mA, tüüp A**Bränd:** Hager**GTIN:** 3250611020233

Rikkevoolukaitse-kaitselüliti, 4-pooluseline, katkestusvõime 6kA, B karakteristik, nimivool 20A, 30mA, tüüp A, ühendab endas rikevoolukaitse ja automaatkaitselüliti funktsioonid, pakkudes tõhusat kaitset nii rikkevoolu, ülekoormuse ja lühise eest. Tüüp A rikevoolukaitse reageerib nii vahelduv- kui ka pulseerivatele alalisvoolu lekkevooludele, sobides kaasaegsetesse elektripaigaldistesse. 4-pooluseline lahendus võimaldab kõigi pooluste samaaegset lahutamist, tagades maksimaalse ohutuse rikete korral. Seade sobib kasutamiseks nii elamu- kui ka äripaigaldistes.

ETIM-teave:

| | |
|---|--|
| Pooluste arv (kokku) | 4 |
| Kaitstud pooluste arv | 4 |
| Tunnuspinge | 400 V |
| Isolatsiooni nimipinge U_i | 500 V |
| Tunnus-impulstaluvuspinge U_{imp} | 4 kV |
| Tunnusvool | 20 A |
| Nimeline rikkevool | 0.03 A |
| Lekkevoolu tüüp | A |
| Voolu piirav klass | 3 |
| Lühise murdmisvõime ICN vastavalt EN 61009-1-le | 6 kA |
| Ühenduse katkestamise omadus | Viivitamatult |
| Ülepingevoolu võimsus | 3 kA |
| Pinge liik | AC |
| Sagedus | 50 Hz |
| Vabasti tunnusjoon | B |
| Samaaegne lülitusneutraaljuht | Ei |
| Lukustusseadmega | Jah |
| Ülepinge kategooria | 3 |
| Saasteaste | 2 |
| Ümbritsev temperatuur töö ajal | -25 °C - 40 °C |
| Laius modulaarsete vahemaade arvus | 4 |
| Sisseehitussügavus | 70 mm |
| Tasapinnale paigaldatud paigaldus | Jah |
| Kahjuvastane komistamisvastane versioon | Ei |
| Kaitseaste (IP) | IP20 |
| Ühendatud juhtme ristlõige tahkesüdamikuga | 1 mm ² - 25 mm ² |
| Ühendatud juhtmete ristlõige mitmejuhtmeline | 1 mm ² - 16 mm ² |

Kinnitused / märgistused:



REALOBJECTS PDFReactor®

Evaluation Version

This PDF document was created by an evaluation version of RealObjects PDFReactor 12.3.2 (17644). The evaluation version is fully functional, but includes this information page. It must not be used for production purposes. The information page and all other evaluation notices must not be removed from the PDF file.

NOTE: Conversions in evaluation mode might be slower and the results might have a larger file size than in production mode.

Buy PDFReactor

To buy a PDFReactor license follow this link:

[Buy PDFReactor online](#)

About PDFReactor

RealObjects PDFReactor is a powerful formatting processor for converting HTML and XML documents into PDF. It uses Cascading Style Sheets (CSS) to define page layout and styles. The server-side tool enables a great variety of applications in the fields of ERP, eCommerce and Electronic Publishing.

PDFReactor supports HTML5, CSS3 and JavaScript.

It allows you to dynamically generate PDF documents such as invoices, delivery notes and shipping documents on-the-fly. PDFReactor allows you to easily add server-based PDF generation functionality to your application or service. Since PDFReactor runs on a server, the end-user in general does not need any software other than a PDF viewer.

For more information visit www.pdfreactor.com