



ADM432C

RVK+Kaitselül. 4P 6kA B-32A 30mA - "A"

Bränd: Hager
GTIN: 3250611020257

RVK+Kaitselül. 4P 6kA B-32A 30mA - "A"

ETIM-teave:

Pooluste arv (kokku)	4
Kaitstud pooluste arv	4
Tunnuspinge	400 V
Isolatsiooni nimipinge Ui	500 V
Tunnus-impulssaluvuspinge Uimp	4 kV
Tunnusvool	32 A
Rated fault current	0.03 A
Leakage current type	A
Current limiting class	3
Rated short-circuit breaking capacity Icn according to EN 61009-1	6 kA
Disconnection characteristic	Undelayed
Surge current capacity	3 kA
Pinge liik	AC
Frequency	50 Hz
Vabasti tunnusjoon	B
Concurrently switching neutral conductor	No
With interlocking device	Yes
Over voltage category	3
Pollution degree	2
Ambient temperature during operating	-25 °C - 40 °C
Width in number of modular spacings	4
Sisseehitussügavus	70 mm
Flush-mounted installation	Jah
Anti- nuisance tripping version	No
Degree of protection (IP)	IP2X
Connectable conductor cross section solid-core	1 mm ² - 25 mm ²
Connectable conductor cross section multi-wired	1 mm ² - 16 mm ²

Kinnitused / märgistused:

