



ADM482C

RVK+Kaitselül. 4P 6kA C-32A 30mA - "A"

Bränd: Hager
GTIN: 3250611020332

RVK+Kaitselül. 4P 6kA C-32A 30mA - "A"

ETIM-teave:

| | |
|---|--|
| Pooluste arv (kokku) | 4 |
| Kaitstud pooluste arv | 4 |
| Tunnuspinge | 400 V |
| Isolatsiooni nimipinge Ui | 500 V |
| Tunnus-impulssaluvuspinge Uimp | 4 kV |
| Tunnusvool | 32 A |
| Rated fault current | 0.03 A |
| Leakage current type | A |
| Current limiting class | 3 |
| Rated short-circuit breaking capacity Icn according to EN 61009-1 | 6 kA |
| Disconnection characteristic | Undelayed |
| Surge current capacity | 3 kA |
| Pinge liik | AC |
| Frequency | 50 Hz |
| Vabasti tunnusjoon | C |
| Concurrently switching neutral conductor | No |
| With interlocking device | Yes |
| Over voltage category | 3 |
| Pollution degree | 2 |
| Ambient temperature during operating | -25 °C - 40 °C |
| Width in number of modular spacings | 4 |
| Sisseehitussügavus | 70 mm |
| Flush-mounted installation | Jah |
| Anti- nuisance tripping version | No |
| Degree of protection (IP) | IP2X |
| Connectable conductor cross section solid-core | 1 mm ² - 25 mm ² |
| Connectable conductor cross section multi-wired | 1 mm ² - 16 mm ² |

Kinnitused / märgistused:

