



REALOBJECTS
PDFReactor[®]

A problem has occurred

2026-06-17 10:16:04

Error message:

This license has expired on 2026-05-30.

License Information:

License serial no:	3916
Licensee:	Adeona Oy
Product:	PDFReactor Web Service
Version:	12.0
License Type:	CPU
Amount:	12 Thread(s)
Maintenance Exp. Date:	2026-05-30
Expiration Date:	2026-05-30
Purchase Date:	2015-11-18
Conditions:	[This license is for use on development systems only. It may not be used on staging or productive systems of any kind.]
Sign Date:	2025-06-02 15:12



CDF663D

Rikkevoolukaitse 4P, 10kA, 63A, 30mA, tüüp F

Bränd: Hager

GTIN: 3250611621621

Rikkevoolukaitse, 4-pooluseline (3P+N), katkestusvõime 10kA, nimivool 63A, 30mA, tüüp F, on mõeldud inimeste ja elektripaigaldiste kaitsmiseks rikkevoolude eest. Tüüp F seade sobib eriti hästi rakendustesse, kus kasutatakse invertereid või sagedusmuundureid, pakkudes stabiilset ja töökindlat kaitset. Seade on varustatud alumiste Bi-Connect klemmidega, mis võimaldavad kiiret ja paindlikku ühendamist. Ühendusklemmid on juhtmesisestuskaitsega, tagades ohutu paigalduse. Väline sinine testnupp ja rikkevoolu indikaator võimaldavad lihtsat kontrolli ja selget oleku jälgimist. Kaitseüliliti on varustatud märgistusaknaga, seda on võimalik üksikult DIN-liistult eemaldada ning vastab IP20 kaitseklassile.

ETIM-teave:

Postide arv	4
Tunnuspinge	400 V
Tunnusvool	63 A
Nimeline rikkevool	0.03 A
Isolatsiooni nimipingeline U _i	500 V
Tunnus-impulssaluvuspinge U _{imp}	4 kV
Võimsuskadu	9.29 W
Paigaldusmeetod	DIN raudtee
Lekkevoolu tüüp	F
Selektiivne kaitse	Ei
Lühiajaline viivitusega komistamine	Jah
Lühise murdmisvõime (ICW)	10 kA
Ülepingevoolu võimsus	5 kA
Pinge liik	AC
Lukustusseadmega	Jah
Sagedus	50 Hz
Võimalik lisavarustus	Jah
Kaitseaste (IP)	IP20
Laius modulaarsete vahemaade arv	4
Sisesehitussügavus	70 mm
Ümbritsev temperatuur töö ajal	-25 °C - 70 °C
Saasteaste	2
Ühendatud juhtmete ristlõige mitmejuhtmeline	1 mm ² - 16 mm ²
Ühendatud juhtmete ristlõige tahkesüdamikuga	1 mm ² - 25 mm ²
RAL-number (sarnane)	7005
Plahvatuskindel	Ei

Kinnitused / märgistused:





REALOBJECTS

PDFReactor®

Evaluation Version

This PDF document was created by an evaluation version of RealObjects PDFReactor 12.3.2 (17644). The evaluation version is fully functional, but includes this information page. It must not be used for production purposes. The information page and all other evaluation notices must not be removed from the PDF file.

NOTE: Conversions in evaluation mode might be slower and the results might have a larger file size than in production mode.

Buy PDFReactor

To buy a PDFReactor license follow this link:

[Buy PDFReactor online](#)

About PDFReactor

RealObjects PDFReactor is a powerful formatting processor for converting HTML and XML documents into PDF. It uses Cascading Style Sheets (CSS) to define page layout and styles. The server-side tool enables a great variety of applications in the fields of ERP, eCommerce and Electronic Publishing.

PDFReactor supports HTML5, CSS3 and JavaScript.

It allows you to dynamically generate PDF documents such as invoices, delivery notes and shipping documents on-the-fly. PDFReactor allows you to easily add server-based PDF generation functionality to your application or service. Since PDFReactor runs on a server, the end-user in general does not need any software other than a PDF viewer.

For more information visit www.pdfreactor.com