



REALOBJECTS

PDFReactor®

A problem has occurred

2026-06-06 05:07:12

Error message:

This license has expired on 2026-05-30.

License Information:

| | |
|------------------------|---|
| License serial no: | 3916 |
| Licensee: | Adeona Oy |
| Product: | PDFReactor Web Service |
| Version: | 12.0 |
| License Type: | CPU |
| Amount: | 12 Thread(s) |
| Maintenance Exp. Date: | 2026-05-30 |
| Expiration Date: | 2026-05-30 |
| Purchase Date: | 2015-11-18 |
| Conditions: | [This license is for use on development systems only. It may not be used on staging or productive systems of any kind.] |
| Sign Date: | 2025-06-02 15:12 |

TUOTEKORTTI

CFA263K



CFA263K

Vikavirtasuojakatkaisija 2-napainen 6kA 63A 300mA tyyppi A

Tuotemerkki: Hager

GTIN: 3250611615910

Sähkönumero: 3260828

Vikavirtasuojakatkaisija (RCD) standardien EN 61008-1, DIN EN 61008-2-1 ja VDE 0664 osa 10 + 11 mukaan, kosketussuojaus IP2x normin DIN VDE 0106 osa 100 mukaisesti. Soveltuu myös jälkiasennettavien ryhmien suojaukseen (kiinnitys ilma työkaluja). Kytkenäliittimet varustettua johdinsivusuojalla. Kaksoisliitin kaapeli- ja virtakiskoliitokselle alapuolella, erillinen sininen testipainike vikavirtapiiriin testaukseen. Moduuli on varustettu saranakantisella merkintäliuskataskulla ryhmämerkintöjä varten.

ETIM-tiedot:

| | |
|--------------------------------------|--|
| Napojen lukumäärä | 2 |
| Nimellijännite | 230 V |
| Nimellisvirta | 63 A |
| Mitoitettu vikavirta | 0.3 A |
| Mitoitettu eristysjännite Ui | 500 V |
| Syöksyjännitekestoisuus Uimp | 4 kV |
| Asennustapa | DIN-kisko |
| Vikavirran tyyppi | A |
| Selektiivinen suojaus | ei |
| Lyhytaikaisesti viivästetty laukaisu | ei |
| Oikosulkukatkaisukyky (Icw) | 6 kA |
| Sykäysvirrankestoisuus | 0.25 kA |
| Jännitetyyppi | AC |
| Lukitsin | ei |
| Taajuus | 50 Hz |
| Lisäyksikkömahdollisuus | kyllä |
| Kotelointiluokka (IP) | IP20 |
| Leveys (moduulipaikkojen määrä) | 2 |
| Upotussyvyys | 70 mm |
| Ympäristön lämpötila käytön aikana | -25 °C - 40 °C |
| Ympäristön likaantumistaso | 2 |
| Liitettävä johdin, monisäikeinen | 1 mm ² - 16 mm ² |
| Liitettävä johdin, lanka | 1 mm ² - 25 mm ² |
| Rajähdyssuojattu | ei |

Hyväksynät / merkinnät:





REALOBJECTS

PDFReactor[®]

Evaluation Version

This PDF document was created by an evaluation version of RealObjects PDFReactor 12.3.2 (17644). The evaluation version is fully functional, but includes this information page. It must not be used for production purposes. The information page and all other evaluation notices must not be removed from the PDF file.

NOTE: Conversions in evaluation mode might be slower and the results might have a larger file size than in production mode.

Buy PDFReactor

To buy a PDFReactor license follow this link:

[Buy PDFReactor online](#)

About PDFReactor

RealObjects PDFReactor is a powerful formatting processor for converting HTML and XML documents into PDF. It uses Cascading Style Sheets (CSS) to define page layout and styles. The server-side tool enables a great variety of applications in the fields of ERP, eCommerce and Electronic Publishing.

PDFReactor supports HTML5, CSS3 and JavaScript.

It allows you to dynamically generate PDF documents such as invoices, delivery notes and shipping documents on-the-fly. PDFReactor allows you to easily add server-based PDF generation functionality to your application or service. Since PDFReactor runs on a server, the end-user in general does not need any software other than a PDF viewer.

For more information visit www.pdfreactor.com