



CP440J

### Strāvas noplūdes automāts 4P 40A 300mA, A - tips, selektīvs

**Zīmols:** Hager

**GTIN:** 3250611616313

Strāvas noplūdes automāts 4P 40A 300mA, A - tips, selektīvs

#### ETIM dati:

Number of poles	4
Rated voltage	400 V
Rated current	40 A
Rated fault current	0.3 A
Rated insulation voltage $U_i$	500 V
Rated impulse withstand voltage $U_{imp}$	4 kV
Mounting method	DIN rail
Leakage current type	A
Selective protection	Yes
Short-time delayed tripping	Yes
Short-circuit breaking capacity ( $I_{cw}$ )	6 kA
Surge current capacity	5 kA
Voltage type	AC
With interlocking device	No
Frequency	50 Hz
Additional equipment possible	Yes
Degree of protection (IP)	IP20
Width in number of modular spacings	4
Built-in depth	70 mm
Ambient temperature during operating	-25 °C - 40 °C
Pollution degree	2
Connectable conductor cross section multi-wired	1 mm <sup>2</sup> - 16 mm <sup>2</sup>
Connectable conductor cross section solid-core	1 mm <sup>2</sup> - 25 mm <sup>2</sup>
Explosion-proof	No

#### Apstiprinājumi / marķējumi:

