PRODUKTDATABLAD
GW95830



GW95830

COMPACT RESIDUAL CURRENT CIRCUIT BREAKER - MDC 100 - CURVE C - 2P 32A 30mA - 2 MODULES

Merke: GEWISS
GTIN: 8011564762435
Elnummer: 4334604

90 RCD Range Modular circuit breakers for residual current protection - The 90 RCD range meets any ground fault protection requirement for any area of application. The range comprises MDC compact residual current c.b. with overcurrent protection. (from 6 to 32 A, curves B and C, up to 10 kA and I?n from 30 and 300 mA type AC, A, A[IR] and A[S] and F) BD and BDHP, add-on residual current devices for circuit breakers MT and MTHP (I?n from 10 mA to 3 A type AC, A, A[IR], A[S] and A adjustable) IDP residual current circuit breakers (up to 125 A, I?n from 10 to 500 mA type AC, A, A[IR], A[S], F, B).

ETIM data:

Antall beskyttede poler	2
Merkespenning	230 V
Nominell isolasjonspenning Ui	500 V
Merkespenningstyrke Uimp	4000 kV
Merkestrøm	6 A
Nominell feilstrøm	0.03 A
Lekkasjestrømtype	A
Energibegrensningsklasse	3
Nominell brytekapasitet etter IEC 60947-2	10 kA
Nominell kortslutningskapasitet Icn iflg. EN 61009-1	10 kA
Utkoblingskarakteristikk	Ikke forsinket
Spenningstype	AC
Frekvens	50 Hz
Utløsningskarakteristikk	C
Medkoblende nulleder	Nei
Med forriglingsmekanisme	Nei
Overspenningskategori	3
Forurensningsgrad	2
Omgivelsestemperatur under drift	-25 °C - 40 °C
Bredde i antall modulmellomrom	2
Innbyggingsdybde	68 mm
Innfelt montasje	Nei
Beskyttelse mot feilutløsing	Nei
Beskyttelsesklasse IP	IP20
Tilkoblingsbart ledertverrsnitt entrådet	1.5 mm² - 25 mm²
Tilkoblingsbart ledertverrsnitt flertrådet	1.5 mm² - 16 mm²

Godkjenninger: