



HIM306

Ümberlüüti 3P, 63A, 5,5 mod.

Bränd: Hager

GTIN: 3250613140526

Ümberlüüti 3P, 63A, 5,5 mod.

ETIM-teave:

Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	No
Version as reversing switch	Yes
Number of switches	1
Max. rated operation voltage Ue AC	415 V
Rated operating voltage	380 V - 415 V
Rated permanent current Iu	63 A
Rated permanent current at AC-23, 400 V	63 A
Rated permanent current at AC-21, 400 V	63 A
Rated short-time withstand current Icw	1.5 kA
Rated operation power at AC-23, 400 V	28 kW
Switching power at 400 V	41 kW
Conditioned rated short-circuit current Iq	50 kA
Number of poles	3
Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as change-over contact	0
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No
Device construction	Built-in device fixed built-in technique
Suitable for floor mounting	Yes
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	Yes
Suitable for intermediate mounting	No
Colour control element	Grey
Interlockable	Yes
Degree of protection (IP), front side	IP20

Kinnitused / märgistused:

