



HMB199

Automātiskais slēdzis 1P 15kA B-125A 1,5M

Zīmols: Hager

GTIN: 3250613230036

Automātiskais slēdzis 1P 15kA B-125A 1,5M

ETIM dati:

Built-in depth	70 mm
Release characteristic	B
Number of poles (total)	1
Number of protected poles	1
Rated current	125 A
Rated voltage	415 V
Rated insulation voltage U_i	500 V
Rated impulse withstand voltage U_{imp}	6 kV
Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 230 V	15 kA
Voltage type	AC
Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 400 V	15 kA
Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 230 V	15 kA
Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 400 V	15 kA
Frequency	50 Hz - 60 Hz
Flush-mounted installation	Jā
Concurrently switching neutral conductor	No
Over voltage category	3
Pollution degree	3
Additional equipment possible	Yes
Width in number of modular spacings	1.5
Degree of protection (IP)	IP20
Ambient temperature during operating	-25 °C - 70 °C
Connectable conductor cross section multi-wired	1 mm ² - 50 mm ²
Connectable conductor cross section solid-core	1 mm ² - 70 mm ²
Explosion-proof	No

Apstiprinājumi / marķējumi:

