



HMB199

### Automātiskais slēdzis 1P 15kA B-125A 1,5M

**Zīmols:** Hager

**GTIN:** 3250613230036

Automātiskais slēdzis 1P 15kA B-125A 1,5M

#### ETIM dati:

Built-in depth	70 mm
Release characteristic	B
Number of poles (total)	1
Number of protected poles	1
Rated current	125 A
Rated voltage	415 V
Rated insulation voltage $U_i$	500 V
Rated impulse withstand voltage $U_{imp}$	6 kV
Rated short-circuit breaking capacity $I_{cn}$ according to EN 60898 at 230 V	15 kA
Voltage type	AC
Rated short-circuit breaking capacity $I_{cn}$ according to EN 60898 at 400 V	15 kA
Rated short-circuit breaking capacity $I_{cu}$ according to IEC 60947-2 at 230 V	15 kA
Rated short-circuit breaking capacity $I_{cu}$ according to IEC 60947-2 at 400 V	15 kA
Frequency	50 Hz - 60 Hz
Flush-mounted installation	Jā
Concurrently switching neutral conductor	No
Over voltage category	3
Pollution degree	3
Additional equipment possible	Yes
Width in number of modular spacings	1.5
Degree of protection (IP)	IP20
Ambient temperature during operating	-25 °C - 70 °C
Connectable conductor cross section multi-wired	1 mm <sup>2</sup> - 50 mm <sup>2</sup>
Connectable conductor cross section solid-core	1 mm <sup>2</sup> - 70 mm <sup>2</sup>
Explosion-proof	No

#### Apstiprinājumi / marķējumi:

