



A problem has occurred

2026-06-18 08:55:13

Error message:

This license has expired on 2026-05-30.

License Information:

License serial no:	3916
Licensee:	Adeona Oy
Product:	PDFReactor Web Service
Version:	12.0
License Type:	CPU
Amount:	12 Thread(s)
Maintenance Exp. Date:	2026-05-30
Expiration Date:	2026-05-30
Purchase Date:	2015-11-18
Conditions:	[This license is for use on development systems only. It may not be used on staging or productive systems of any kind.]
Sign Date:	2025-06-02 15:12



MCS140

Automatiniai jungikliai QC 1 P 6kA C kreivė 40A QC**Prekės ženklas:** Hager**GTIN:** 3250614315220

Automatiniai jungikliai su „QuickConnect“ greito prijungimo gnybtų technologija •standartai DIN EN 60898-1, IEC 60898-1, VDE 0641-11
 •energijos ribojimo klasė 3 •atskirus įrenginius galima atjungti nuo šynų sistemos •greito prijungimo išėjimai iki 20 A •greito prijungimo jėgimas iki 63 A •papildomus modulius galima įdiegti vėliau •apsauga nuo prisilietimo pagal DIN VDE 0106 100 •žymėjimo langelis •greito prijungimo automatiniai jungikliai suderinami su visais HAGER 6 ir 10kA automatiniais jungikliais

ETIM duomenys:

Suprojektuotas gylis	70 mm
Išleidimo charakteristika	C
Polių skaičius (bendras)	1
Apsaugotų polių skaičius	1
Nustatyta srovė	40 A
Nustatyta įtampa	400 V
Nominali izoliacinė įtampa Ui	500 V
Nurodytoji atlaikoma impulsinė įtampa	4 kV
Nurodytoji trumpojo jungimo nutraukimo geba pagal EN60898 prie 230 V	6 kA
Įtampos tipas	Maiņstrāvas
Nurodyta trumpojo jungimo nutraukimo geba Icu pagal IEC 60947-2 ir 230 V	10 kA
Dažnio diapazonas	50 Hz - 60 Hz
Galios nuostolis	4.8 W
Srovės apribojimo klasė	3
Lygiai montuojama instaliacija	Taip
Šiuo metu perjungiantis į N neutralią padėtį	Ne
Įtampos paviršiaus kategorija	3
Užterštumo laipsnis	2
Galima papildoma įranga	Ne
Modulinių tarpų skaičius plotyje	1
Saugos laipsnis (IP)	IP20
Aplinkos temperatūra operaciniu metu	-25 °C - 70 °C
Prijungiamo laidininko kryžminės sekcijos įvairialypis laidynas	1 mm ² - 25 mm ²
Prijungiamo laidininko kryžminės sekcijos vientisa šerdis	1 mm ² - 35 mm ²
Apsaugotas nuo sprogo	Ne

Patvirtinimai / ženklėjimas:



REALOBJECTS

PDFReactor®

Evaluation Version

This PDF document was created by an evaluation version of RealObjects PDFReactor 12.3.2 (17644). The evaluation version is fully functional, but includes this information page. It must not be used for production purposes. The information page and all other evaluation notices must not be removed from the PDF file.

NOTE: Conversions in evaluation mode might be slower and the results might have a larger file size than in production mode.

Buy PDFReactor

To buy a PDFReactor license follow this link:

[Buy PDFReactor online](#)

About PDFReactor

RealObjects PDFReactor is a powerful formatting processor for converting HTML and XML documents into PDF. It uses Cascading Style Sheets (CSS) to define page layout and styles. The server-side tool enables a great variety of applications in the fields of ERP, eCommerce and Electronic Publishing.

PDFReactor supports HTML5, CSS3 and JavaScript.

It allows you to dynamically generate PDF documents such as invoices, delivery notes and shipping documents on-the-fly. PDFReactor allows you to easily add server-based PDF generation functionality to your application or service. Since PDFReactor runs on a server, the end-user in general does not need any software other than a PDF viewer.

For more information visit www.pdfreactor.com