



NCN163

### Automātslēdzis MCB 1P 6kA C-63A 1M

**Zīmols:** Hager

**GTIN:** 3250614614682

Automātslēdzis MCB 1P 6kA C-63A 1M

#### ETIM dati:

|  |  |
|--|--|
| Built-in depth   | 70 mm                                  |
| Release characteristic   | C                                      |
| Number of poles (total)  | 1                                      |
| Number of protected poles  | 1                                      |
| Rated current  | 63 A                                   |
| Rated voltage  | 400 V                                  |
| Rated insulation voltage $U_i$   | 500 V                                  |
| Rated impulse withstand voltage $U_{imp}$  | 6 kV                                   |
| Rated short-circuit breaking capacity $I_{cn}$ according to EN 60898 at 230 V    | 10 kA                                  |
| Voltage type   | AC                                     |
| Rated short-circuit breaking capacity $I_{cu}$ according to IEC 60947-2 at 230 V | 15 kA                                  |
| Frequency  | 50 Hz - 60 Hz                          |
| Power loss   | 5.73 W                                 |
| Current limiting class   | 3                                      |
| Flush-mounted installation   | Jā                                     |
| Concurrently switching neutral conductor   | No                                     |
| Over voltage category  | 3                                      |
| Pollution degree   | 2                                      |
| Additional equipment possible  | Yes                                    |
| Width in number of modular spacings  | 1                                      |
| Degree of protection (IP)  | IP20                                   |
| Ambient temperature during operating   | -25 °C - 70 °C                         |
| Connectable conductor cross section multi-wired                                  | 1 mm <sup>2</sup> - 25 mm <sup>2</sup> |
| Connectable conductor cross section solid-core                                   | 1 mm <sup>2</sup> - 35 mm <sup>2</sup> |
| Explosion-proof  | No                                     |

#### Apstiprinājumi / marķējumi:

