



NCN304

### Kaitselüliti 3P 10kA C-4A, 3 mod.

**Bränd:** Hager

**GTIN:** 3250614614880

Kaitselüliti 3P 10kA C-4A, 3 mod.

#### ETIM-teave:

|                                                                             |                |
|-----------------------------------------------------------------------------|----------------|
| Sissehitussügavus                                                           | 70 mm          |
| Vabasti tunnusjoon                                                          | C              |
| Pooluste arv (kokku)                                                        | 3              |
| Kaitstud pooluste arv                                                       | 3              |
| Tunnusvool                                                                  | 4 A            |
| Tunnuspinge                                                                 | 400 V          |
| Isolatsiooni nimipinge Ui                                                   | 500 V          |
| Tunnus-impulssstaluvsing Uimp                                               | 6 kV           |
| Lühisvoolu tunnuslahutusvõime Icn standardi EN 60898 järgi pingel 230 V     | 10 kA          |
| Pinge liik                                                                  | AC             |
| Lühisvoolu tunnuslahutusvõime Icn standardi EN 60898 järgi pingel 400 V     | 10 kA          |
| Lühisvoolu tunnuslahutusvõime Icu standardi EN 60947-2 järgi pingel 230 V   | 30 kA          |
| Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V | 15 kA          |
| Frequency                                                                   | 50 Hz - 60 Hz  |
| Current limiting class                                                      | 3              |
| Flush-mounted installation                                                  | Jah            |
| Concurrently switching neutral conductor                                    | No             |
| Over voltage category                                                       | 3              |
| Pollution degree                                                            | 2              |
| Additional equipment possible                                               | Yes            |
| Width in number of modular spacings                                         | 3              |
| Degree of protection (IP)                                                   | IP20           |
| Ambient temperature during operating                                        | -25 °C - 70 °C |
| Connectable conductor cross section multi-wired                             | 1 mm² - 25 mm² |
| Connectable conductor cross section solid-core                              | 1 mm² - 35 mm² |
| Explosion-proof                                                             | No             |

#### Kinnitused / märgistused:

